

A Great Fit for New or Existing Desktop Applications! Value based thermal transfer printing



Simple and Intuitive

Easy to load ribbon, accessible label path and single button control enable clear and trouble-free operation.



Cost-Effective Compatibility

The CL-S321 offers EPL2 compatibility, so you can just plug and print with existing applications. Convenient to use and economically priced, the CL-S321 is a great choice for value-based thermal transfer printing.

CITIZEN CL-S321/331
LABEL

Applications

- Retail
- Healthcare
- Pharmacy
- E-Seller
- SME / SMB



Compact Size and Efficient Design

The compact and efficient design helps to reduce desktop space usage and makes the CL-S321 a great fit for all thermal transfer applications.



3 interfaces as default

With full speed USB 2.0, RS232C serial, 10/100 Ethernet interfaces standard the CL-S321 is flexible and ready to fit into your applications both old and new!



CITIZEN CL-S321/331

LABEL

Specifications

Models	CL-S321	CL-S331
Technology	Thermal Transfer/Direct Thermal	
Resolution	203 dpi (8 dots per mm)	300dpi (12 dots per mm)
Print Speed (maximum)	4 inches per second (102 mm/s)	3 inches per second (76.2mm/s)
Print Width (maximum)	4.25 inches (108 mm)	4.16 inches (105.7mm)
Media Width (min to max)	1 inch to 4.64 inches (25.4 mm to 118 mm)	
Media Thickness (min to max)	0.003 to 0.008 inches (0.06 to 0.2 mm)	
Media Sensor	Fixed label gap and black mark	
Media Length (min to max)	1 inch to 68 inches (25.4 mm to 1727 mm)	
Roll Size (max), Core size	5 inches (127 mm) diameter, 1 / 1.5 inches (25,4 mm / 38,1 mm) core	
Interface	USB 2.0, RS-232 and 10/100 Ethernet	
Ribbon Size	1.57 inches (40mm) maximum diameter, 110 metre length, 0.5 inch (12.7mm) cores	
Ribbon Winding & Type	Ink side out. Wax, wax/resin or resin type	
Case	Hi-Open™	
Mechanism	Self-contained	
Panel	One LED, Control key: FEED	
Flash (Non-Volatile Memory)	8MB Flash, 16MB SDRAM	
Windows® drivers and software	Supporting XP®, 2003, 2008, Vista™, 7, 8	
Size (W x D x H) and Weight	224 mm x 254 mm x 170 mm), 2.5 Kg	
Printer, Head Warranty	1 year for Printer; 30 Kms/6 months on head	

Designs, specifications and availability are subject to change without notice. Errors and omissions excluded.

Features & Benefits

- EPL2 programming language compatible
- Hi-Open™ housing for easy media loading
- Self-contained mechanism for durable operation
- Compact design
- Single button control panel
- Auto switching power supply, 100-240V, 50-60Hz
- Fixed label sensor
- Standard tear-bar for perforated tags
- USB 2.0, RS-232 serial and 10/100 Ethernet interfaces standard
- Media roll holder

Dealer stamp